

INSTALLATION INSTRUCTIONS

108182 Two-Shot Trunk Release Relay

This product is designed to minimize the "Unintentional Open Trunk" condition frequently observed with GM vehicles which use the global style key fob remote. Typically, the trunk latch releases for no apparent reason, usually while the vehicle is parked and unattended. Because the trunk release occurs with a single press of the release button, bumping the button unintentionally causes the trunk to open and it's condition is aggravated by the key fob design.

This new relay replaces the factory trunk release relay with a specially-designed electronic module that requires TWO presses of the release button within 3-4 seconds (interior button as well) to open the trunk. With the required two presses within the allotted timeframe, accidental trunk opening is significantly reduced.

Installation is very simple and can be done in less than three minutes with no tools or special knowledge required. You simply access the fuse/relay panel in the vehicle, locate the trunk release relay, pull it out, and plug in the replacement module. Installation into a 2010 and newer Camaro is illustrated below.



Begin by lifting this panel. Grasp the lower edge and pull outward as shown. There are three spring latches that hold it in place and you will only need to release the two lower latches. Note that you don't have to completely remove the panel; just pull it out far enough to access the trunk relay. Pull the relay out of its socket and insert the new relay into its place.



The Two Shot Relay has five pins on the bottom; three on one side, and two on the other side. It can only be inserted one way and cannot be plugged in wrong. Don't force it in; it should plug into its socket easily and with little force.



Pull the factory relay out of its socket and put it in the glovebox. Then, insert the Two-Shot relay into the relay socket. Be sure it goes in properly; there are five pins on the relay and it must be inserted as shown below.



Test by pressing trunk release on the fob (or release button in interior) twice, to open the trunk. Replace panel after verifying operation. That's all there is to it! **Note: You must press the trunk release button TWICE within 3-4 seconds, otherwise, you must repeat the procedure.**