

INSTALLATION INSTRUCTIONS

109036 Dual Fan Controller – Stand Alone

This kit is designed to Plug-And-Play into the readily available Dual Fan assembly, made by Dodge and marketed on the internet. OEM application is 1999 Dodge Intrepid. It's commonly referred to as a "Ramchargers Fan".



Use of this kit assumes you have already installed the dual fan to your vehicle.

Using this kit, you can control both low and high speeds of both fans with the flick of a switch. The switch, mounted in the passenger compartment is a **very unique and miniature switch** that has an LED built into the handle of the switch. It's miniature size requires a single ¼ in. drilled hole for mounting, and the LED will light when the 3-way switch is selected to either low speed or high speed fan operation. UP runs the fans on HIGH, center is OFF, and DOWN is LOW speed.



Installing this harness is simple; you only need a positive feed (battery or alternator stud) and a ground. The switch harness plugs into the main harness, which contains two sealed 30 amp relays.



The "Plug-And-Play" feature of this kit permits simple attachment to the fan connector – NO CUTTING OR CONNECTOR WIRING NEEDED.

Installation is simple
Fasten relays to a suitable location on the inner fender well using the supplied hardware. Attach the fuse linked ring terminal to the battery positive using the supplied long battery bolt and spacer. Attach the black negative terminal to the battery negative. Install the switch into your vehicle and run the wiring connection to the mating connector.

